

BYAF-63 series Weatherproof AC Isolating Switch



Technical Parameter:

- Conform to IEC60947-3
- Rated Current: 40A, 63A
- Rated Voltage: 230~440VAC
- No. of Pole: 3P, 4P
- EESS Approved



Application

ZIBENY The BYAF series of weatherproof isolating switches is a robust range of switches suitable for virtually any external application included in the range are three and four poles switch from 40A to 63A, the base mounted mechanism provides for easier wiring and more wiring room.

Parameter

Designation	BYAF-63	
Pole	3P	4P
Rated Voltage	230~440VAC	230~440VAC
Rated Current	40A	40A
	63A	63A
Rated Frequency	50Hz	
Reted Insulation Voltage	1000V	
Rated Impulse Withstand Voltage	2.5kV	
Rated Duty	Un-interrupted	
Short Term Withstand Current	750 A For 1Sound	
Short Circuit Making Capacity	750A	
Switch Rating	AC-22A(According to IEC 60947-3)	

Wiring Diagram

Contacts Wiring Diagram	230~440V	Poles in series	Type Number	IP Rating	Weight / pcs
	40A 63A	Three poles	BYAF-63	IP65	0.61kgs
	40A 63A	Four poles	BYAF-63	IP65	0.67kgs

Dimensions(mm)

